

MATERIAL SAFETY DATA SHEET



MATERIAL SAFETY DATA SHEET

Product Name: Zenith Quartz

MSDS Date: January 2020

1. PRODUCT AND COMPANY DESCRIPTION

Product Name: Zenith Quartz

Zenith Quartz is a registered trademark Zenith Quartz Surface.

2. HAZARDS IDENTIFICATION

Appearance/Odor: Multi-colored engineered stone with no odor.

Potential Health Effects: Quartz surfaces products are not hazardous as shipped.

Acute Eye: Product in finished form does not present a health hazard via this route of entry. Dusts and flying particles generated during cutting, grinding, and forming may cause irritation and injury.

Acute Skin: Dusts generated from this product may cause skin irritation.

Acute Inhalation: Dusts from product may cause irritation to respiratory tract, nose, throat, and lungs.

Acute Ingestion: Not considered a potential health hazard via this route of entry. This product may cause gastrointestinal irritation of dusts are swallowed.

Chronic Exposure: The adverse health effects from crystalline silica exposure – silicosis, cancer, scleroderma, tuberculosis, and nephrotoxicity – are chronic effects.

Aggravation of Pre-existing Conditions: Not determined.



3. HAZARDOUS CHEMICAL COMPOSITION

COMPONENT	CAS #	% COMPOSITION
Crystalline Silica (quartz) and other natural stone	14808 – 60 - 7	>90
Resins and trace minerals including Al ₂ O ₃ , Fe ₂ O ₃ , TiO ₂ , CaO, MgO, Na ₂ O, K ₂ O..	N/A	Balance

4. FIRST AID MEASURES

Eye Exposure: Immediately flush eyes with copious amounts of water for a minimum of 15 minutes. Seek immediate medical attention if adverse effect occurs.

Skin Exposure: Wash skin with soap and water. Remove exposed or contaminated clothing, taking care not to contaminate eyes. Seek medical attention if adverse effect occurs.

Inhalation: Remove person to fresh air. If necessary, use artificial respiration.

5. FIRE FIGHTING MEASURES

Quartz Surface Products can be combusted only with difficulty. Decomposition products resulting from the polymer and pigments degrading at elevated temperatures include various hydrocarbons, carbon dioxide, carbon monoxide and water. Fumes of metal oxides and mica particles could also be released.

Extinguishing Media

Water, Dry Chemical, CO₂, Foam.

Fire Fighting Instructions

Keep personnel removed and upwind of fire. Wear self-contained breathing apparatus.



6. ACCIDENTAL RELEASE MEASURES

Clean up and Disposal of Spill: Solid slabs can simply be gathered, as necessary. If large amounts of dust or wastes are created by cutting process, vacuum or sweep up material avoiding dust generation or dampen spilled material with water to avoid airborne dust. Wear sufficient respiratory protection and protective clothing where necessary. If large quantities of this material enter the waterways, contact the Environmental Protection Authority, or local Waste Management Authority. Dispose of waste in accordance with local, state, and federal regulations.

7. HANDLING AND STORING

Handling/Storage:

- ✓ Avoid breathing dust. Wash hands before eating, drinking smoking, or using toilet facilities.
- ✓ Wash thoroughly after work using soap and water.
- ✓ Good industrial hygiene practices should be followed when handling this material.
- ✓ Product is heavy and breakable; handle with care to avoid injury and prevent damage.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the MSDS. General room ventilation is satisfactory under anticipated use conditions.

Personal Protective Equipment

Respiratory Protection: In case of insufficient ventilation, wear appropriate respiratory equipment in compliance with local regulations.

Eye / Face Protection: During cutting, grinding or sanding operations safety glasses with side shields or goggles should be worn.

Skin Protection: During cutting, grinding or sanding operations use body protection appropriate for the task including work gloves if handling sharp or rough edges and steel-toed shoes if lifting product.



9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Appearance: Multi-colored engineered stone

Odor: None

pH: NA

Specific Gravity: 2.2-2.5

Water Solubility: Insoluble

Flash Point: 490 C

Melting Point: NA

Boiling Point: NA

Vapor Pressure: NA

% Volatiles: NA

Viscosity: NA

10. STABILITY AND REACTIVITY

Chemical Stability: Stable

Conditions to Avoid: None

Materials/Chemicals to be Avoided: This product is incompatible with hydrofluoric acid. Silica will dissolve in hydrofluoric acid and produce the corrosive gas silicon tetrafluoride.

Hazardous Decomposition Products: Upon decomposition, various hydrocarbons, carbon dioxide, carbon monoxide fumes, and water may be released.

Hazardous Polymerization: Will not occur.



11. TOXICOLOGICAL INFORMATION

The powder generated in the manufacturing processes contains silica (SiO₂).

Prolonged and/or massive inhalation of crystalline silica can cause pulmonary fibrosis and pneumoconiosis and silicosis, as well as a worsening of other pulmonary diseases (bronchitis, emphysema, etc.) The main symptom of silicosis is the loss of pulmonary capacity. People with silicosis have a greater risk of getting lung cancer.

12. ECOLOGICAL INFORMATION

Environmental Fate: Not Determined

Environmental Toxicity: Not Determined

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose in accordance with federal, state, and local requirements.

14. TRANSPORTATION INFORMATION

Not classified as dangerous in the meaning of transport regulations.

15. REGULATORY INFORMATION

U.S. Federal Regulations

TSCA Inventory Status: In compliance with TSCA Inventory requirements for commercial purposes.



16. OTHER INFORMATION

National Fire Protection Association NFPA (R) and Hazardous Materials Identification System (HMIS)

Hazard Ratings:

Health Hazard: 1

Flammability: 0

Reactivity: 0

Key Legend Information:

IDLH – Immediately Dangerous to Life and Health

N/A – Not Applicable

PEL – Permissible Exposure Limit

ND – Not Determined

TWA – Time Weighted Average

ACGIH – American Conference of Governmental Industrial Hygienists

STEL – Short Term Exposure Limit

NTP – National Toxicology Program

OSHA – Occupational Safety and Health Administration

TLV – Threshold Limit Value

The data in the Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

